





ESCAPE SERIES

TREK 59" X 82"


SEATING	4-5 Adults (Bench, bucket and lounge seating)
DIMENSIONS	59" x 82" x 38" (Fits through most exterior doorways)
DRY WEIGHT	750 lbs
WATER CAPACITY	260 - 310 gallons
HYDROTHERAPY JETS	14 Duo-Tone; Graphite Gray Jets 
DIGITAL CONTROLS	Top side control with digital read out.
LIGHTING	4" Underwater LED
WATERFALL	Optional
ICEBUCKET	None
SHELL	ABS backed Acrylic Shell with Acrylobond substructure.
SURROUND CABINET	Highwood: Gray, Brown, Mahogany or Tan
INSULATION	Five Stage Arctic Seal
ELECTRICAL	220 volt 50 amp
PUMPS	2.0 Horsepower, 56 frame, 2-speed, 220 volts and 1/15 horsepower circulation pumps.
HEATER	5.5kw, stainless steel, with flow through housing.
FILTER	50 square foot with telescopic filter basket.
OZONATOR	Ozone water purification system, corona discharge standard.
PILLOWS	Standard
WARRANTY	5 year shell. 1 year no fault.
COVER	UL Approved Safety Cover




SHELL COLOR OPTIONS




Silver Birch




Storm Cloud



Tuscan Sun



Sterling Silver



Pacific Rim



Alabaster Wave



Sahara



Smoky Mountain

SKIRT COLOR OPTIONS



Gray



Brown



Mahogany



Tan

ESCAPE SERIES - TREK

Seating: 4-5 Adults (Bench, bucket and lounge seating)
 Water Capacity: 260 - 310 gallons
 Dry Weight: 750 lbs
 Hydrotherapy Jets: 14 Duo-Tone; Graphite Gray Jets
 Digital Controls: Top Side control with digital readout and 4 button auxiliary control.
 Lighting: 4" Underwater LED Light
 Waterfall: Optional
 Ice Bucket: None
 Shell: ABS backed Acrylic Shell with Acrylobond substructure.
 Surround Cabinet: Highwood: Redwood, Gray, Brown, Mahogany or Tan
 Insulation: Five Stage Arctic Seal
 Electrical: 220 volt 50 amp
 Pumps: 2.0 Horsepower, 56 frame, 2-speed, 220 volts and 1/15 horsepower circulation pumps.
 Heater: 5.5kw, stainless steel, with flow through housing.
 Filter: 50 square foot with telescopic filter basket.
 Ozonator: Ozone water purification system, corona discharge standard.
 Pillows: Standard
 Warranty: 5 year shell. 3 year no fault.
 Cover: UL Approved Safety Cover

